

low temperature

Percival® model LT41VL

Constant Defrost Temperature



applications

- This chamber is frequently used to measure cold hardness, freeze tolerance, heat stress and exposure to a series of temperatures
- Many other applications exist for this product
Please compare your own requirements to the specifications listed below.

percival's IntellusUltra controller

Percival Scientific has built a reputation of providing flexible, customized options for research scientists around the world. We've taken that philosophy to the next level with our improved IntellusUltra Controller. Now choose from the levels of functionality that meet your research needs.

Please refer to www.percival-scientific.com for additional information regarding the control system.

lighting system

- Two externally mounted lampbanks (F25T8/741 fluorescent) reduce interior heat load while eliminating need to open chamber and remove shelves when changing light bulbs
- Externally mounted lamp banks separated from chamber growth space by glass side wall

lighting system (continued)

- Glass is evenly heated over its entire surface eliminating condensation
- Intensity programmable up to 450 $\mu\text{moles}/\text{m}^2/\text{s}$ of light irradiance measured @ 6" from lamps on 2 on/off light events (without drop-off due to low temperature)
- Programming and control of the lighting is done via IntellusUltra real time controller

insulation

- Woodless construction using CFC free insulation (overall wall thickness is 2" [5.1 cm], ample insulation for maintenance of stated temperature range)

door

- One door opening 37.2" x 57.5" (94.4 cm x 146 cm) provides full access to the chamber interior (magnetic gasket provides a tight seal to door frame)

LT-41VL specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers	
	°C	ft ³	m ³	ft ²	m ²	in	cm	width		depth		height			
								in	cm	in	cm	in	cm	$\mu\text{moles}/\text{m}^2/\text{s}$	
(-10-44±0.5	37.2	1.1	13.6	1.3	*	*	49.8	126.5	33.6	85.4	77.2	196.1	450	2	

*21.5" with 2 shelves or 43.8" with 1 shelf

low temperature Percival model LT41VL

cabinet construction

- Interior constructed of 22-gauge electro-zinc plated steel
- Exterior constructed of 18-gauge exterior electro-zinc plated steel
- Welded seams and joints on outer and inner shells
- Inner shell supported by non-compressing/non-thermal conducting material locking inner liner in place without a metal-to-metal bond to outer case
- Each side wall has evenly heated glass with viewing dimensions of 37" x 21.5"
- Externally mounted lamp banks on each side wall (if enough room is allowed on side of chamber, lamp banks swing like a door allowing full view of each shelf without disturbing the experiment [allow clearance when replacing bulbs])

interior space

- 37.2 ft³ (1.1 m³) with work area of 13.6 ft² (1.3 m²) provided on two tiers

shelving

- Two tiers of white epoxy coated steel wire shelving (each shelf is 27"D x 32.6"W [68.6 cm x 82.8 cm])
- Shelves are vertically adjustable in ½" increments
- Maximum growing height is 43.8" for one shelf and 21.5" for two shelves

finish

- Interior and exterior painted with highly reflective, environmentally friendly, high temperature baked white powder coating

refrigeration

- Constant temperature defrost allows chamber to operate at low temperature under full lighting without temperature defrost spikes (typically, low temperature systems are defrosted by the diversion of hot gas through the coil or via electric heaters, causing a significant temperature spike during the defrost period)
- Dual coil system has been utilized in order to maintain a constant low temperature within chamber
- Coils work in tandem with a damper system (as one coil is cooling, the other coil is defrosted via hot gas)
- An air flow damper switches with coils preventing the coil being defrosted from putting its heat into system (coil being defrosted is essentially closed off from rest of the system)
- Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and close temperature control (this continuous running condensing unit ensures precise temperature control and provides defrost of cooling coils via hot gas with out the need of electric heaters)

refrigeration (continued)

- Optional outdoor all weather air-cooled condensing unit or self contained water-cooled condensing unit available upon request

temperature range

- -10°-44°C (±0.5°C) lights on and -12°-44°C (±0.5°C) lights off (chamber gives greater temperature uniformity, and allows for lower temperature limit under full lighting)

temperature safety limit controls

- (Experiment Protection) Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- Controls shut down all power to the chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

options (most popular)

- IntellusUltra Connect (C9)
- IntellusUltra Connect and Android-based Touchscreen (C9T)
- IntellusUltra (standard) and Android-based Touchscreen (C8T)
- CO₂ enrichment package
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Dimmable lighting (closed loop with PAR light sensor) (Q22)
- Dimmable lighting (open loop control) (Q23)
- Extended temperature ranges available

See other catalog sheets or consult factory for additional accessories.

convenience receptacles

- Two 115/1/60 convenience receptacles provided inside chamber

electrical service requirements

- 120-208/1/60 with NEMA L14-30P plug provided (with standard chamber)
- RLA=15, MCA=18.8



Percival Scientific, Inc.
505 Research Drive • Perry, IA 50220 USA
800.695.2743 • 515.465.9363 • Fax: 515.465.9464
www.percival-scientific.com