

# plant tissue culture

## Percival® model CU-41L5



CU-41L4 chamber shown

### applications

- This chamber is specifically designed for Plant tissue culture on plates/dishes or in flasks
- Many other applications exist for this product  
*Please compare your own requirements to the specifications listed below.*

### percival's IntellusUltra controller

Percival Scientific has built a reputation of providing flexible, customized options for research scientists around the world. We've taken that philosophy to the next level with our improved IntellusUltra Controller. Now choose from the levels of functionality that meet your research needs.

*Please refer to [www.percival-scientific.com](http://www.percival-scientific.com) for additional information regarding the control system.*

### lighting system

- Each tier of shelves lighted by lamps properly spaced for uniform light intensity over entire shelf
- Intensity programmable up to 220  $\mu\text{moles}/\text{m}^2/\text{s}$  of light irradiance measured @ 6" from lamps on 2 on/off light events
- Programming and control of the lighting is done via IntellusUltra real time controller

### cabinet construction

- 26-gauge smooth galvanized white side walls and top reinforced with 24-gauge backer plates
- Interior floor constructed of 24-gauge #304-4 stainless steel
- 24-gauge smooth white galvanized exterior
- NSF compliant seam design
- Overall wall thickness 2"
- Foamed-in-place non-CFC insulation (refer to insulation section)
- One 1¼" diameter access port on right hand wall
- Chamber floor equipped with floor drain and hose assembly
- Contains casters assembly and adjustable leveling legs to compensate for floor unevenness in the lab

## CU-41L5 specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers
	°C	ft <sup>3</sup>	m <sup>3</sup>	ft <sup>2</sup>	m <sup>2</sup>	in	cm	width		depth		height		
10-44±0.5	37.2	1.1	34	3.2	5.2	13.2	41	104.1	33.6	85.4	77.2	196.1	220 @ shelf	5

All specifications are per compartment unless otherwise noted.

# plant tissue culture Percival model CU41L5

## airflow/circulation

- Conditioned air circulates through a rear wall duct and is picked up by a specially designed fixed air diffuser located at the bottom of each tier (air is then delivered vertically upward at a slow speed through each shelf)
- Air diffuser insulates shelf level experiments from heat generated by underlying light fixture (this design minimizes condensation on dish lids)

## insulation

- Woodless construction using 2" thick foamed-in-place non-CFC Urethane insulation with 93% closed cell, R-value of 12.5, K-value of 0.16 and density of 2.2 lbs/ft<sup>3</sup>

## door

- One door opening 36.8" x 57.5" (93.5 cm x 146 cm) provides full access to the chamber interior (magnetic gasket provides a tight seal to door frame)

## interior space

- 37.2 ft<sup>3</sup> (1.1 m<sup>3</sup>) with work area of 34 ft<sup>2</sup> (3.2 m<sup>2</sup>) provided on four shelves

## shelving

- Four tiers of white epoxy coated steel wire shelving (each shelf is 27"D x 36.3"W [68.6 cm x 92.1 cm])
- Shelves slide in and out easily on stainless steel rail assemblies
- Maximum growing height is 5.2" (13.2 cm)

## finish

- Interior and exterior painted with highly reflective, environmentally friendly, high temperature baked white powder coating

## refrigeration

- Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and close temperature control (this continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; this also prolongs life of compressor, and eliminates risk of ice build up in coil)
- Solenoid valves have an extended stem for quiet and long life operation
- Ceiling mounted evaporator coil incorporates twin air circulation fans in aluminum housing (heat rejection to ambient [standard chamber] = 3400 BTU/hr.)

## temperature range

- 10°-44°C (±0.5°C) lights on and 2°-44°C (±0.5°C) lights off

## temperature safety limit controls

- (Experiment Protection) Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- Controls shut down all power to the chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

## options (most popular)

- IntellusUltra Connect (C9)
  - IntellusUltra Connect and Android-based Touchscreen (C9T)
  - IntellusUltra (standard) and Android-based Touchscreen (C8T)
  - Ultrasonic Humidifier with advanced RH Sensor (H11)
  - Dehumidification via independent dehumidifying coil with reheat heaters and Ultrasonic Humidifier (H12)
  - Ultrasonic Humidifier with Electronic RH sensor (H14)
  - CO<sub>2</sub> enrichment package
  - Door with observation window and cover (Q2)
  - Door with fresh air ports (Q1)
  - Self-contained water-cooled condensing unit
  - Dry alarm contacts
  - Dimmable lighting (closed loop with PAR light sensor) (Q22)
  - Dimmable lighting (open loop control) (Q23)
  - Extended temperature ranges available
- See other catalog sheets or consult factory for additional accessories.*

## convenience receptacles

- Two 115/1/60 convenience receptacles provided inside chamber

## electrical service requirements

- 115/1/60 - two grounded cords each with NEMA 5-15P plug provided for standard chamber
- Cord #1 RLA=8.4 & cord #2 RLA=9.5 (combined MCA=22.4)



Percival Scientific, Inc.  
505 Research Drive • Perry, IA 50220 USA  
800.695.2743 • 515.465.9363 • Fax: 515.465.9464  
[www.percival-scientific.com](http://www.percival-scientific.com)