

arabidopsis

Percival® model AR-95L2

Standard SciWhite™ lighting



applications

- This chamber is frequently used for *Arabidopsis thaliana*, *Brassica sp.*, lettuce, spinach and other plants with low to medium light intensity requirements
- Many other applications exist for this product

Please compare your own requirements to the specifications listed below.

IntellusUltra controller

The IntellusUltra control system (C8) was purpose-built for controlled environments and is standard on all Percival chambers.

- Robust and reliable, industrial-grade integrated hardware design
- Highly flexible architecture facilitates configuration, expansion and customization
- Precise, simultaneous control of up to 7 environmental parameters
- Industry-leading experiment protection and system diagnostics

IntellusUltra control graphical user interface

A touchscreen user interface is provided as standard on all Percival Scientific plant growth chambers and allows users to interact with their controlled environment in new and intuitive ways.

- 10.1" IPS, high resolution display with 10-point multi-touch sensitivity
- Tabular and graphical presentation of chamber programs and parameters
- Highly visible process values and alarm notifications
- Enhanced user feedback menus

Please refer to www.percival-scientific.com for additional information regarding the control systems.

SciWhite LED lighting system

- Two tiers of lighted shelving lit by SciWhite LEDs
- Intensity programmable up to 575 $\mu\text{moles/m}^2/\text{s}$ of light irradiance measured @ 6" from LEDs
- Programming and control of the lighting is done via IntellusUltra real time controller
- Dimmable between 10-100% output

airflow/circulation

- Air circulation inside chamber is from a specifically designed air diffuser (air travels along the entire back wall, over the shelves and returns to the ceiling fans through an opening between the light fixtures and the doors)

cabinet construction

- Interior constructed of 24-gauge galvanized steel
- Interior floor constructed of 22-gauge polished stainless steel
- Exterior constructed of 24-gauge Galvannealed extra-smooth steel
- Overall wall thickness is 2" (5.1 cm)
- Integrated floor drain
- Contains casters assembly and adjustable leveling legs
- One 1.25" access port with air-tight plug
- Highly durable and reflective coating

AR-95L2 specifications (subject to change without notice)

| Temp Range with all lights on | Interior Space volume | | Total Shelving Floor Area | | Maximum Growing Height | | Exterior Dimensions | | | | | | Light Intensity 6" from lamps unless otherwise noted | Tiers |
|----------------------------------|--------------------------|-----|------------------------------|-----|---------------------------|----|---------------------|-------|-------|------|--------|-------|--|-------|
| | | | | | | | width | | depth | | height | | | |
| °C | ft³ | m³ | ft² | m² | in | cm | in | cm | in | cm | in | cm | µmoles/m²/s | |
| 7-44±0.5 | 95.9 | 2.7 | 28.6 | 2.7 | 27.6 | 70 | 95.9 | 243.5 | 37.1 | 94.3 | 78.5 | 199.4 | 575 | 2 |

arabidopsis Percival model AR-95L2

insulation

- Woodless construction using foam-in-place 2" [5.1 cm] thick CFC free urethane insulation foam (this is an environmentally friendly foam with global warming potential [GWP] of 0.0 and ozone depletion potential [ODP] of 0.0)

doors

- Two reach-in doors each with an opening of 29" x 57.3" (73.7 cm x 145.4 cm) providing full access to chamber interior
- Magnetic gasket provides a tight seal to door frame

interior space

- 95.9 ft³ (2.7 m³) with work area of 28.6 ft² (2.7 m²) provided on two tiers

shelving

- Two tiers of stainless steel shelving (each shelf is 36.8"W x 28"D [95.3 cm x 71.1 cm])
- Each shelf is supported by shelf clips allowing ½" vertical adjustments
- Maximum growing height is 27.6" (70 cm) per tier

refrigeration

- Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and tight temperature control. Continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; also prolongs compressor life, and eliminates risk of ice build up in coil.
- Extended stem solenoid valves for quiet and long life operation
- Heat rejection to the ambient (standard refrigeration system) = 4,144 BTU/hr.

temperature range

- 2°-44°C (±0.5°C) lights off and 7°-44°C (±0.5°C) lights on (full fresh air) within work area on horizontal plane with lights on

temperature safety limit controls

- (Experiment Protection) Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- Controls shut down all power to the chamber, activating alarms
- System automatically resets when temperature returns to normal range

humidity control (optional)

- Ultrasonic Humidifier with Advanced RH Sensor (H11)
- Ultrasonic Humidifier and Dehumidifier with Advanced RH Sensor (H12)
- Ultrasonic Humidifier with Electronic RH sensor (H14)
- Ultrasonic Humidifier and Dehumidifier with Electronic RH sensor (H15)

See other specification sheets or consult factory for additional information.

options (most popular)

- IntellusUltra Connect (C9)
- Additive CO₂ control
- CO₂ removal system
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Closed loop dimmable lighting with PAR light sensor (Q22)
- Open loop dimmable lighting per tier (Q23+)
- Extended temperature ranges available
- Convenience receptacles

Contact info@percival-scientific.com with questions or for additional information.

electrical service requirements

- 120/208-230/1/60 (4-wire, plus ground) with direct-wire field connection terminals
- RLA=11 (MCA=13.8)

regulatory standards

- Electrical Safety: UL-508A, certified and labelled by Percival Scientific under UL file number E340161
- Quality System: ISO 9001:2015, certified under DQS, Inc. under certification number 10017261

helping you create better science

Percival Scientific controlled environment systems are the culmination of over 60 years of design and manufacturing experience. Our high quality products have been developed through direct partnerships with the scientific community and offer platforms that are highly customizable and provide superior performance. We understand that scientific innovation is bred through creativity, passion, technical expertise and attention to detail, and we are proud to help you create better science.



Percival Scientific, Inc.
505 Research Drive • Perry, IA 50220 USA
800.695.2743 • 515.465.9363 • Fax: 515.465.9464
www.percival-scientific.com